LEX L11 mission-critical te device

MADE FOR THE MISSION AHEAD

WHEN HARDWARE, SOFTWARE, AND ACCESSORIES WORK SEAMLESSLY TOGETHER, THE RESULT IS A DEVICE THAT WORKS SEAMLESSLY FOR YOU.

Introducing the LEX L11 Mission-Critical LTE Device, designed for public safety users. Every feature and function has been thoughtfully considered in this rugged device to make it easy to operate. It boasts loud and clear audio, intuitive operation, and long battery life.

Rugged and durable yet streamlined and slim, you can count on the LEX L11 to perform when it's needed most.

KEY FEATURES

INTUITIVE CONTROLS

- Dedicated Push-To-Talk Button
- Dedicated Emergency Button
- Dedicated Talkgroup Rocker Switch
- Two Programmable Buttons

HIGH QUALITY AUDIO PERFORMANCE

- Noise and Echo Cancellation
- Dual Front Facing Loud Speakers
- Howling Suppression
- Holster with Audio Tunneling Technology

PERFORMS EVEN IN THE HARSHEST ENVIRONMENTS

- MIL-STD-810G for Drop and Shock
- IP-67 rated

SECURE MOBILE PLATFORM

- Mobile Device Management
- Secure Boot, Integrity Monitoring, and Device Malware Blocking
- End-to-end security with CRYPTR micro hardware enables FIPS-140-2 Level 3

RADIO COLLABORATION

- Remote Control Radio's Folders, Channels and Volume
- Remote Emergency button capability for TETRA and ASTRO radios

MOTOROLA

♥ 🕸 🎽 📋 10:40

Q.

1

X

1

0

A O %

PSX PTT

LondonIC2 No activity

LondonIC1

LondoniC2

Q

 Remote Speaker Microphone (RSM) capability for TETRA and ASTRO radios

ACCESSORIES SUITE

- Standard and High Capacity Battery Options
- Field Swappable Battery
- Fast Charging
- Holsters, Vehicle and Desktop Cradles, Single and Multi Unit Chargers and 3.5 mm Headsets



GENERAL SPECIFICATIONS

CONNECTIVITY		
	NA: 4, 5, 7, 12, 14, 17, 29, 30, 66 APAC and LA: 1, 2, 3, 4, 5, 7, 8, 19, 28 EMEA: 3, 7, 20, 38, 39, 40	
LTE Bands:	GSM: 850 MHz, 900 MHz, 1800 MHz, 1900 MHz	
	UMTS: 2100 MHz, 1900 Mhz, 1700 MHz, 900 MHz, 850 MHz	
Bluetooth	Bluetooth 4.2 Low Energy	
GPS, NFC	Standalone GPS, Assisted GPS (aGPS), NFC	
Wi-Fi - Operating Band	2.4 GHz, 5 GHz	
Wi-Fi - Standards	802.11 a/b/g/n/ac/k/r	
BATTERY		
Capacity	Field swappable IMPRES 2 Standard Capacity - 2,500 mAH High-Capacity - 5,000 mAH	
Battery Life	Standard Capacity - 10 hours High-Capacity - 20 hours	
PHYSICAL		
Dimensions (H x W x D) With Standard Battery	152.5 mm x 78 mm x 13.2 mm	
Dimensions (H x W x D) With High-Capacity Battery	152.5 mm x 78 mm x 19.2 mm	
Weight With Standard Battery	260 g	
Weight With High-Capacity Battery	310 g	
Ruggedness and Durability	Continues to run after multiple drops to concrete from a height of 4 Feet (121 cm) Drop tested using MIL-STD-810G Method 516.7, Procedure IV	
,	IP67 (1 meter water immersion for 30 minutes)	
Operating Temperature	-20°C to +55°C	
Storage Temperature	-46°C to +85°C storage for 72 hours	
SECURITY		
SD Card	CRYPTR micro FIPS 140-2 Level 3 VAILIDATED Certification #2876	
Integrity Monitoring	Standard	
Root Detection	Standard	
Multi-Factor Authentication	Optional	
Mobile Virtual Private Network	Optional	
Remote Configuration	Trusted 3rd Party Provided	
OTA Firmware and Software Upgrades	Trusted 3rd Party Provided	
Application Whitelisting	Trusted 3rd Party Provided	
Over-the-Air Wipe and Lock	Trusted 3rd Party Provided	
Secure Boot	Standard	
Integrity Monitoring	Standard	

HARDWARE		TOP VIEW
Display	127mm (5.0 in) 1280 x 720 pixels Capacitive, touch-screen with Gorilla Glass	Netification
Memory	4 GB RAM 64 GB Internal Storage Storage is expandable with external 128 GB microSD™ card	- Notification LEDs Dedicated Emergency
Camera	Rear 13 MP Auto Focus High-Output LED Flash Digital Zoom Front 8 MP	Button
Sensor Platform	Fingerprint Sensor Proximity Sensor with Gesture Sensor Ambient Light Sensor Accelerometer Barometer Gyroscope E-Compass	Talkgroup Rocker Switch
Ports	USB 3.0 type C connector 3.5 mm audio (stereo)	-
Mission Critical Buttons	Dedicated PTT Button Dedicated Emergency Button Talkgroup Rocker Switch 2 Programmable Buttons Power Button Volume (Up / Down) Buttons	SIDE VIEW
SOFTWARE		
Operating System	Android 7.1 Nougat	
Google Mobility Services (GMS)	Enabled	Dedicated Push-To-Talk Button
Input	Three microphones for superior noise suppression and echo cancellation	
Output	106 dBSPL at 5 cm 98 dBphon at 30 cm	
DEVICE MANAGEN	IENT	Volume Control
Remote management and configuration	Supports OMA-DM (Open Mobile Alliance Device Management)	
VIDEO AND IMAGI	NG	2 Programmable
Supported Formats	H.263, H.264, MPEG-4 SP, VP8, JPEG (,jpg), GIF (.gif), PNG (.png), BMP (.bmp), WebP, (.webp) Formats Supported for Playback, Streaming, and Recording	Buttons
Supported File Types	3GPP (.3gp), MPEG-4 (.mp4), WebM (.webm), (.mkv)	
Video Recording Quality	4K (UHD) at 30 fps 1080p (FHD) at 60 fps	

For more information, please visit

www.motorolasolutions.com/LEXL11

Motorola Solutions Ltd. Nova South, 160 Victoria Street, London, SW1E 5LB, United Kingdom.

MOTOROLA, MOTO, MOTOROLA SOLUTIONS and the Stylized M Logo are trademarks or registered trademarks of Motorola Trademark Holdings, LLC and are used under license. All other trademarks are the property of their respective owners. © 2019 Motorola Solutions, Inc. All rights reserved.



Airsys Communications Technology Ltd 35 City Industrial Park Southern Road Southampton SO15 1HG www.airsys.co.uk +44.238.071.8700



Standard

Malware Blocking